

















## 24V LED DRIVERS

## Constant Voltage Drivers

LEDs using these drivers require a 24V DC constant voltage input with a parallel wiring method. Max 10m.  
Example fittings that use these drivers include: LD Picture Light, LD11, LD Line 15, LD22

| 24V<br>Constant Voltage Drivers  |            |  |  |  |  |  |  |  |
|----------------------------------|---|---|---|---|---|---|---|---|
|                                  | TXDA24008   | TXDTC24016DALI  | TXDTC24020DIM   | TX.DTR24018S  | TXDTR24035S   | TXDTR24060S   | TXDTR24100S   | TXDTR24200S   |
| <b>Brand</b>                     | TCI   | TCI   | TCI   | Tridonic  | Tridonic  | Tridonic  | Tridonic  | Tridonic  |
| <b>Output power (W)</b>          | 8W  | 16W   | 20W   | 18W   | 35W   | 60W   | 100W  | 200W  |
| <b>Dimmable</b>                  | use with Dimming Controller   | Integrated Dimming (DALI) controller  | Integrated Dimming (1-10) controller  | Use with dimming controller   | use with Dimming Controller   | use with Dimming Controller   | use with Dimming Controller   | use with Dimming Controller   |
| <b>Output voltage (V)</b>        | 24V DC  | 24V DC  | 24V DC  | 24V DC  | 24V DC  | 24V DC  | 24V DC  | 24V DC  |
| <b>Dimensions L x W x H (mm)</b> | 60 x 35 x 22  | 111 x 52 x 22   | 111 x 52 x 22   | 127 x 43x 30  | 142 x 43 x 30   | 225 x 43 x 30   | 295 x 43 x 30   | 325 x 43 x 30   |
| <b>IP rating</b>                 | Drivers can be supplied with an IP rated box for use in wet environments (sold separately). |   |   |   |   |   |   |   |
| <b>Warranty</b>                  | 5 years   | 5 years   | 5 years   | 5 years   | 5 years   | 5 years   | 5 years   | 5 years   |

| 24V<br>Constant Voltage<br>Mains Dimmable Drivers |          |
|---|---|
|   | TXDEC24060PHD   |
| <b>Brand</b>                                      | Ecopac Power  |
| <b>Output power (W)</b>                           | 60W   |
| <b>Dimmable</b>                                   | 240V leading edge dimmable  |
| <b>Output voltage (V)</b>                         | 24V DC  |
| <b>Dimensions L x W x H (mm)</b>                  | 178 x 61 x 24   |
| <b>IP rating</b>                                  | Drivers can be supplied with an IP rated box for use in wet environments (sold separately). |
| <b>Warranty</b>                                   | 3 years   |

| 24V Dimming<br>Controllers       |  UL                    |  UL |  UL |  UL |  UL |  UL |  UL |
|----------------------------------|---|--|---|--|--|--|--|
|                                  | TXDO-DIM  | TXDO-DIM DALI  | TXDEL-DIM   | TXDEL-DIM DALI   | TXDEL-DIM DMX  | TXDEL-DIM DMX 2CH  | TXDEL-DIM RGBW DMX   |
| <b>Brand</b>                     | Osram   | Osram  | eldoLED   | eldoLED  | eldoLED  | eldoLED  | eldoLED  |
| <b>Output power (W)</b>          | 0 - 120W  | 0 - 240W   | 192W  | 192W   | 192W   | 192W   | 4 x 36W  |
| <b>Number of channels</b>        | 1   | 4  | 1   | 1  | 1  | 2  | 4  |
| <b>Dimmable</b>                  | 1 - 10V (0 - 100%)  | DALI/DALI-2 (0 - 100%)   | 0-10V (0 - 100%)  | DALI (0 - 100%)  | DMX (0 - 100%)   | DMX (0 - 100%)   | DMX (0 - 100%)   |
| <b>Output voltage (V)</b>        | 24V DC  | 24V DC   | 24V DC  | 24V DC   | 24V DC   | 24V DC   | 24V DC   |
| <b>Dimensions L x W x H (mm)</b> | 172 x 42 x 20   | 181 x 42 x 20  | 153 x 50 x 23   | 153 x 50 x 23  | 153 x 50 x 23  | 153 x 50 x 23  | 153 x 50 x 23  |
| <b>IP rating</b>                 | Dimming controllers can be supplied with an IP rated box for use in wet environments (sold separately). |  |   |  |  |  |  |
| <b>Warranty</b>                  | 3 years   | 3 years  | 5 years   | 5 years  | 5 years  | 5 years  | 5 years  |

Please Note: Dimming drivers must be tested with control systems to assess compatibility. Dimming range can vary depending on the manufacturer of the dimmer / control system.